

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method for preserving confidentiality of an electronic mail from a sender to a recipient, comprising:
 - authenticating identity information of the recipient;
 - restricting the recipient's ability to modify contents of the electronic mail based on a confidentiality level established by the sender, wherein a user interface is to comprise a first set of confidentiality levels from which the sender is to select irrespective of the recipient's email address;
 - encrypting the electronic mail, at the recipient, with the authenticated identity information if the recipient attempts to store the electronic mail to a local storage; and
 - decrypting the electronic mail, at the recipient if the recipient attempts to retrieve the electronic mail from the local storage.
2. (Original) The method according to claim 1, wherein the identity information is a system password.
3. (Original) The method according to claim 1, the method further comprising:
 - prompting a user of the recipient to supply the identity information;
 - decrypting the electronic mail with the identity information supplied by the user.
4. (Original) The method according to claim 1, the method further comprising:
 - asserting a control signal to disable options that are originally supported by the recipient if the confidentiality level satisfies a predefined confidentiality threshold.
5. (Previously Presented) The method according to claim 4, wherein the control signal is a control signal.

6. (Currently Amended) An electronic mail confidentiality preserver of a recipient email client, comprising:
 - an input-processing engine to limit abilities of a user of the recipient email client to modify contents of an electronic mail received by the recipient email client based on a confidentiality level, wherein a user interface further comprises a first set of confidentiality levels from which a user of a sender email client is to select irrespective of the recipient's email address; and
 - an encryption/decryption engine, coupled to the input-processing engine, to encrypt the electronic mail with authenticated identity information if the recipient attempts to store the electronic mail to a local storage.
7. (Original) The electronic mail confidentiality preserver according to claim 6, the input-processing engine further asserts a first control signal to disable options that are originally supported by the email client if the confidentiality level satisfies a predefined confidentiality threshold.
8. (Previously Presented) The electronic mail confidentiality preserver according to claim 7, wherein the first control signal is a control signal.
9. (Original) The electronic mail confidentiality preserver according to claim 6, the input-processing engine further asserts a second control signal to invoke the encryption/decryption engine in response to the user's access.
10. (Original) The electronic mail confidentiality preserver according to claim 6, the encryption/decryption engine further
 - prompts the user for identity information;
 - if the user's access to the local storage is to store the electronic mail, encrypts the electronic mail with the identity information; and
 - if the user's access to the local storage is to retrieve the electronic mail, decrypts the electronic mail with the identity information.

- 11 (Currently Amended) A electronic mail clients, comprising:
- a user interface;
 - a communication engine;
 - a local storage;
 - and an electronic mail confidentiality preserver, coupled to the user interface, coupled to the communication engine and coupled to the local storage, wherein the electronic mail confidentiality preserver further comprises:
 - an input-processing engine to limit abilities of a user of the recipient email client to modify contents of an electronic mail received by the recipient email client based on a user-selected confidentiality level, ~~irrespective of the recipient's email address~~; and
 - an encryption/decryption engine, coupled to the input-processing engine, to encrypt the electronic mail with authenticated identity information if the recipient attempts to store the electronic mail to a local storage, wherein the user interface further comprises a first set of confidentiality levels from which a user is to select.
12. (Currently Amended) The electronic mail client according to claim 11, wherein the user interface further comprises:
- ~~a first set of confidentiality levels for the user to select from; and~~
 - a second set of options to manipulate the electronic mail from which ~~[[for]]~~ the user is to select ~~[[from]]~~.
13. (Original) The electronic mail client according to claim 12, wherein the electronic mail confidentiality preserver further asserts a first control signal to the user interface to disable selected options from the second set of options if the confidentiality level satisfies a predefined confidentiality threshold.

14. (Previously Presented) The electronic mail client according to claim 13, wherein the first control signal is a control signal.
15. (Original) The electronic mail client according to claim 12, the input-processing engine further asserts a second control signal to invoke the encryption/decryption engine in response to the user's access.
16. (Original) The electronic mail client according to claim 12, the encryption/decryption engine further
 - prompts the user for identity information;
 - if the user's access to the local storage is to store the electronic mail, encrypts the electronic mail with the identity information; and
 - if the user's access to the local storage is to retrieve the electronic mail, decrypts the electronic mail with the identity information.
17. (Currently Amended) A storage device including a plurality of instructions readable therefrom, the instructions, when executed by a computer system, cause the computer system to perform operations comprising:
 - authenticating identity information of a recipient of an electronic mail;
 - restricting the recipient's ability to modify contents of the electronic mail based on a confidentiality level established by a sender of the electronic mail, wherein a user interface is to comprise a first set of confidentiality levels from which the sender is to select irrespective of the recipient's email address;
 - encrypting the electronic mail with the authenticated identity information if the recipient attempts to store the electronic mail to a local storage; and
 - decrypting the electronic mail if the recipient attempts to retrieve the electronic mail from the local storage.

18. (Currently Amended) The ~~machine-readable-medium~~ storage device according to claim 17, wherein the identity

information is a system password.

19. (Currently Amended) The ~~machine-readable-medium~~ storage device according to claim 17, the instructions further comprising:

prompting a user of the recipient to supply the identity information;

decrypting the electronic mail with the identity information supplied by the user.

20. (Currently Amended) The ~~machine-readable-medium~~ storage device according to claim 17, the instructions further comprising:

asserting a control signal to disable options that are originally supported by the recipient if the confidentiality level satisfies a predefined confidentiality threshold.

21. (Currently Amended) The ~~machine-readable-medium~~ storage device according to claim 20, wherein the control signal is a control signal.